



BS EN3  
KM No. 577694

## BSI Portable Foam Fire Extinguishers

### Description

Foam Extinguishers are made of high quality ST14 by means of deep drawing.

Foam Fire Extinguishers are effective on class A & B fire.

Corrosive and impact resistant polyester paint finish (powder coating).

All Extinguishers are coated internally for optimal protection against rust and corrosion.

AFFF is an extinguishing agent which seals the burning surface against ignition.

The valve provided with safety release valve to release the excess pressure.

These extinguishers are manufactured according to international Standards and approved by local civil defence in U.A.E.

Cylinders of different capacity can be supplied upon request.

Foam Fire Extinguishers are available in cream color also.



### Specification

Model	FF6L	FF9L
Classification	AB	AB
KM No.	577694	577694
Fire Rating	13A/144B	21A/183B
Extinguishing Agent	3% AFFF	3% AFFF
Hydrostatic Test Pressure	30 Bar	30 Bar
Operating Pressure	15 Bar	15 Bar
Propellant	Dry Nitrogen	Dry Nitrogen
Max. Temp. Range	0°C to +60°C	0°C to +60°C
Agent Volume	6 Ltr.	9 Ltr.
Total Mass	8.5 Kg.	14.14 Kg.
Discharge Time	13 Sec.	37 Sec.