



Product: <u>6220UJ</u>

Fire Alarm, #16-2c BC, FPLP

Product Description

Fire Alarm Cable, Plenum-FPLP, 2-16 AWG solid bare copper conductors with FEP insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

	Fire Ala	rm, Addressabl	e Systems, Cir	cuits: Audio, Control, Initiating	g, Notification
Construction Det	ails				
Conductor					
Element No. of E	lements Size	Stranding	Material		
Conductor(s) 2	16 AWG	Solid BC	C - Bare Coppe	r	
nsulation					
Element	Material	No	m. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s) FEP - Fl	uorinated Ethylene F	Propylene 0.00	7 in (0.18 mm)	0.066 in (1.7 mm)	Black, Red
Duter Shield					
Material					
No Shield					
Outer Jacket				I	
Material	Nom. Thickness				
PVC - Polyvinyl Chlorid	0.015 in (0.38 mm	n) 0.162 in	Yes		
Overall Cable Diameter	(Nominal): 0.162 ir	ו			
	. ,				
Electrical Charac	teristics				
Electrical Charac Electricals Nom. Conductor DCR	teristics Nom. Capacitanc	e Cond-to-Con		k. Current	
Electrical Charac	teristics	e Cond-to-Con		x. Current Conductor at 25°C	
Electrical Charac Electricals Nom. Conductor DCR	teristics Nom. Capacitanc	e Cond-to-Con			
Electrical Charact Electricals Nom. Conductor DCR 4.26 Ohm/1000ft	teristics Nom. Capacitanc	e Cond-to-Con			
Electrical Charact Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage	teristics Nom. Capacitanc	e Cond-to-Con			
Electrical Charac Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating 300 V	teristics Nom. Capacitanc 26 pF/ft (85 pF/m)	e Cond-to-Con			
Electrical Charac Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating	teristics Nom. Capacitanc 26 pF/ft (85 pF/m)	e Cond-to-Con			
Electrical Charac Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating 300 V	teristics Nom. Capacitanc 26 pF/ft (85 pF/m)	e Cond-to-Con			
Electrical Charact Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Charact	teristics Nom. Capacitanc 26 pF/ft (85 pF/m)	e Cond-to-Con			
Electrical Charact Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Charact Temperature	teristics Nom. Capacitanc 26 pF/ft (85 pF/m)	e Cond-to-Con			
Electrical Charact Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Charact Temperature	teristics Nom. Capacitanc 26 pF/ft (85 pF/m) acteristics	e Cond-to-Con			
Electrical Charact Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Charact Temperature UL Temperature Op 75°C 0°C	teristics Nom. Capacitanc 26 pF/ft (85 pF/m) acteristics	e Cond-to-Con			
Electrical Charac Electricals Nom. Conductor DCR 4.26 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Chara Temperature UL Temperature Op 75°C 0°C Bend Radius	teristics Nom. Capacitanc 26 pF/ft (85 pF/m) Acteristics Rerating To +75°C	e Cond-to-Con			

Bulk Cable Weight:	22 lbs/1000ft				
Standards and Compliance					
Environmental Suitability:	Indoor				
Flammability / Reaction to Fire:	NFPA 262 (UL910)				
NEC / UL Compliance:	Article 760, FPLP				
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEB				
APAC Compliance:	China RoHS II (GB/T 26572-2011)				
Other Standard Compliance(s):	California State Fire Marshall				
Product Notes					
Froduct Notes					
Notes:	Teflon® is a trademark of DuPont.				

Notes:		Tetion® is a trademark of DuPont.		
	History			
	Update and Revision:	Revision Number: 0.305 Revision Date: 05-05-2023		

Part Numbers

Variants

Item #	Color	UPC	Footnote
6220UJ 0021000	Red	612825174363	С

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.